


# Premier Pass Thru Refrigerators

## Premier Pass Thru Refrigerators

These units feature both front and rear door access for applications where the loading and removal of product from both sides of the unit is required. Pass-Thru units are ideal for clean room and pharmacy IV preparation applications. The Premier Pass-Thru Refrigerators also feature a microprocessor temperature controller that allows for precise temperature control, recovery and maintenance versus mechanical dial thermostats. Samples and supplies are protected with an extensive package of temperature security and alarm features. In addition, a large digital display and solution bottle are installed to provide an accurate indication of sample temperatures.



The Premier Pass Thru Refrigerators are also purpose built for critical cold storage applications, but where built-in data logging functionality may not be a necessity.

The all-new temperature display and alarm module offers an array of robust security features with a monitoring and alarm system that is 100% independent of a microprocessor temperature controller.



Available in either sliding or swinging glass front doors. Two solid rear swinging doors.



ABT-HCPTP-49

Model	Cu. Ft.	Defrost	Front Door	Back Door	Shelves	W"	D"	H"	RL	H.P.	Amps
ABT-HCPTP-47	47	Cycle	2 Glass	2 Solid	8 Adj	54 1/8	32 3/8	78 5/8	R290a	1/2	8.8
ABT-HCPTP-49	49	Cycle	2 Glass	2 Solid	8 Adj	54 1/8	33 7/8	78 5/8	R290a	1/2	8.5

- Microprocessor Temperature Controller
- Adjustable operating temperature range: 1° -10° C
- Digital Temperature Display and Alarm Module
- Sample simulated digital temperature display; 1° Resolution
- Adjustable temperature display in Celsius or Fahrenheit
- Audible and visual high/low temperature alarms
- Sensor error alarm
- Power failure alarm
- Resettable 1-point Min/Max History
- Remote alarm contacts
- Alarm validation (audible, visual, and remote alarm)
- Alarm mute with ring back
- Keyed door lock
- Magnetic door gasket for positive seal
- Heavy duty door handle
- Casters (adds 4" to height)
- One probe access port (3/8")
- White textured cabinet and door
- High density urethane foam cabinet and door insulation
- HFC-free refrigerant (R290a), foam insulation and packaging
- Two year parts and labor warranty, plus an additional three year compressor parts warranty
- Quality certified with 100% unit temperature testing
- Cycle defrost
- UL/C-UL listed