



The Standard Laboratory Refrigerators take a large step forward in performance from past solid door general purpose units; offering a digital temperature display and alarm module coupled with a microprocessor temperature controller.



°C/F convertible temperature display.

ABT-LS-16

ABT-LS-36

Model	Cu. Ft.	Defrost	Doors	Shelves	W"	D"	H"	RL	H.P.	Amps
ABT-HC-SLS-12	12	Cycle	1 Swing Solid	3 Adj	25	29 3/4	63 3/4	R134a	3/8	6
ABT-SLS-16	16	Cycle	1 Swing Solid	3 Adj	25	29 3/4	77	R134a	3/8	6
ABT-SLS-23	23	Cycle	1 Swing Solid	4 Adj	26 7/8	34 3/4	79 3/4	R134a	3/8	6
ABT-HC-SLS-26	26	Cycle	1 Swing Solid	4 Adj	28 3/8	36 1/2	79 3/4	R134a	3/8	6
ABT-SLS-36	36	Cycle	2 Swing Solid	8 Adj	39 5/8	34 3/4	79 3/4	R134a	1/2	9
ABT-SLS-49	49	Cycle	2 Swing Solid	8 Adj	54	34 3/4	79 3/4	R134a	1/2	7
ABT-HC-SLS-72	72	Cycle	3 Swing Solid	12 Adj	81	34	79 3/4	R134a	3/4	10

- LED interior lights are safety shielded and switch controlled
- Probe access port (3/8")
- Powder coated steel white interior and exterior
- High density urethane foam cabinet insulation

- CFC-free refrigerant (R134a), foam insulation and packaging
- One year parts and labor warranty, plus an additional four year compressor parts warranty
- UL/C-UL listed