

Product Name:	ABT-HC-12S
Description:	<p>Premier Solid Door Laboratory Refrigerator  12 Cu. Ft. capacity  One swing solid door, self-closing, right hinged, not reversible  Microprocessor Temperature Controller  Adjustable operating temperature range: 1°-10°C  Standard Digital Temperature Display and Alarm Module with battery back-up to support temperature monitoring and alarms  Sample simulated digital temperature display; .1° Resolution  Adjustable temperature display in Celsius or Fahrenheit  Audible and visual high/low temperature alarms  2 probes; 1 in air and 1 in sample bottle  Sensor error alarm  Power failure alarm  Resettable 1-point Min/Max History  Remote alarm contacts  Alarm validation (audible, visual, and remote alarm)  Alarm mute with ring back  Three adjustable shelves (adjustable in ½" increments)  Forced draft air circulation  Keyed door lock  LED interior lights are safety shielded and switch controlled  Swivel casters (3 ½")  probe access port (3/8")  White powder-coated steel exterior and interior  Hydrocarbon, natural refrigerant (R290)  Two year parts and labor warranty, plus an additional three compressor parts warranty  Exterior dimensions: 25" W x 29 ¾" D x 65 ¾" H with casters; 62 ¼" H without casters  Cycle defrost  115V, 60 Hz, 3 Amps, 1/5 HP  ETL listed  Shipping weight: 227 lbs.</p>

Product Name:	ABT-16S
Description:	<p>Premier Solid Door Laboratory Refrigerator  16 Cu. Ft. capacity  One swing solid door, self-closing, right hinged, not reversible  Microprocessor Temperature Controller  Adjustable operating temperature range: 1°-10°C  Standard Digital Temperature Display and Alarm Module  Sample simulated digital temperature display; .1° Resolution  Adjustable temperature display in Celsius or Fahrenheit  Audible and visual high/low temperature alarms  Sensor error alarm  Power failure alarm  Resettable 1-point Min/Max History  Remote alarm contacts  Alarm validation (audible, visual, and remote alarm)  Alarm mute with ring back  Three adjustable shelves (adjustable in ½" increments)  Keyed door lock  Magnetic door gasket for positive seal  Heavy duty door handle  LED interior lights are safety shielded and switch controlled  Casters with footed brake  probe access port (3/8")  White powder-coated steel exterior and interior  CFC-free refrigerant (R134a), foam insulation and packaging  Two year parts and labor warranty, plus an additional three  compressor parts warranty  Quality certified with 100% unit temperature testing  Exterior dimensions: 25"W x 29 ¾"D x 77"H  Cycle defrost  115V, 60 Hz, 6 Amps, 3/8 HP  UL/C-UL listed  Shipping weight: 277 lbs.</p>

Product Name:	ABT-23S
Description:	<p>Premier Solid Door Laboratory Refrigerator  23 Cu. Ft. capacity  One swing solid door, self-closing, right hinged, not reversible  Microprocessor Temperature Controller  Adjustable operating temperature range: 1°-10°C  Standard Digital Temperature Display and Alarm Module  Sample simulated digital temperature display; .1° Resolution  Adjustable temperature display in Celsius or Fahrenheit  Audible and visual high/low temperature alarms  Sensor error alarm  Power failure alarm  Resettable 1-point Min/Max History  Remote alarm contacts  Alarm validation (audible, visual, and remote alarm)  Alarm mute with ring back  Four adjustable shelves (adjustable in ½" increments)  Keyed door lock  Magnetic door gasket for positive seal  Heavy duty door handle  LED interior lights are safety shielded and switch controlled  Casters with footed brake  probe access port (3/8")  White powder-coated steel exterior and interior  CFC-free refrigerant (R134a), foam insulation and packaging  Two year parts and labor warranty, plus an additional three  compressor parts warranty  Quality certified with 100% unit temperature testing  Exterior dimensions: 26 7/8"W x 34 3/4"D x 79 3/4"H  Cycle defrost  115V, 60 Hz, 6 Amps, 3/8 HP  UL/C-UL listed  Shipping weight: 321 lbs.</p>

Product Name:	ABT-HC-26S
Description:	<p>Premier Solid Door Laboratory Refrigerator  26 Cu. Ft. capacity  One swing solid door, self-closing, right hinged, not reversible  Microprocessor Temperature Controller  Adjustable operating temperature range: 1°-10°C  Standard Digital Temperature Display and Alarm Module with battery back-up to support temperature monitoring and alarms  Sample simulated digital temperature display; .1° Resolution  Adjustable temperature display in Celsius or Fahrenheit  Audible and visual high/low temperature alarms  2 probes; 1 in air and 1 in sample bottle  Sensor error alarm  Power failure alarm  Resettable 1-point Min/Max History  Remote alarm contacts  Alarm validation (audible, visual, and remote alarm)  Alarm mute with ring back  Four adjustable shelves (adjustable in ½" increments)  Forced draft air circulation  Keyed door lock  Magnetic door gasket for positive seal  Heavy duty door handle  LED interior lights are safety shielded and switch controlled  Swivel casters (3 ½")  probe access port (3/8")  White powder-coated steel exterior and interior  Hydrocarbon, natural refrigerant (R290)  Two year parts and labor warranty, plus an additional three compressor parts warranty  Exterior dimensions: 28 ¾" W x 36 ½" D x 81 ¾" H with casters; 78 ¼" H without casters  Cycle defrost  115V, 60 Hz, 3 Amps, 1/5 HP  ETL listed  Shipping weight: 275 lbs.</p>

Product Name:	ABT-36S
Description:	<p>Premier Solid Door Laboratory Refrigerator  36 Cu. Ft. capacity  Two swing solid doors, self-closing, right hinged, not reversible  Microprocessor Temperature Controller  Adjustable operating temperature range: 1°-10°C  Standard Digital Temperature Display and Alarm Module  Sample simulated digital temperature display; .1° Resolution  Adjustable temperature display in Celsius or Fahrenheit  Audible and visual high/low temperature alarms  Sensor error alarm  Power failure alarm  Resettable 1-point Min/Max History  Remote alarm contacts  Alarm validation (audible, visual, and remote alarm)  Alarm mute with ring back  Eight adjustable shelves (adjustable in ½" increments)  Keyed door lock  Magnetic door gasket for positive seal  Heavy duty door handle  LED interior lights are safety shielded and switch controlled  Casters with footed brake  probe access port (3/8")  White powder-coated steel exterior and interior  CFC-free refrigerant (R134a), foam insulation and packaging  Two year parts and labor warranty, plus an additional three  compressor parts warranty  Quality certified with 100% unit temperature testing  Exterior dimensions: 39 5/8"W x 34 3/4"D x 79 3/4"H  Cycle defrost  115V, 60 Hz, 9 Amps, 1/2 HP  UL/C-UL listed  Shipping weight: 422 lbs.</p>

Product Name:	ABT-49S
Description:	<p>Premier Solid Door Laboratory Refrigerator  49 Cu. Ft. capacity  Two swing solid doors, self-closing, right hinged, not reversible  Microprocessor Temperature Controller  Adjustable operating temperature range: 1°-10°C  Standard Digital Temperature Display and Alarm Module  Sample simulated digital temperature display; .1° Resolution  Adjustable temperature display in Celsius or Fahrenheit  Audible and visual high/low temperature alarms  Sensor error alarm  Power failure alarm  Resettable 1-point Min/Max History  Remote alarm contacts  Alarm validation (audible, visual, and remote alarm)  Alarm mute with ring back  Eight adjustable shelves (adjustable in ½" increments)  Keyed door lock  Magnetic door gasket for positive seal  Heavy duty door handle  LED interior lights are safety shielded and switch controlled  Casters with footed brake  probe access port (3/8")  White powder-coated steel exterior and interior  CFC-free refrigerant (R134a), foam insulation and packaging  Two year parts and labor warranty, plus an additional three  compressor parts warranty  Quality certified with 100% unit temperature testing  Exterior dimensions: 54"W x 34 ¾"D x 79 ¾"H  Cycle defrost  115V, 60 Hz, 7 Amps, 1/2 HP  UL/C-UL listed  Shipping weight: 528 lbs.</p>

Product Name:	ABT-HC-72S
Description:	<p>Premier Solid Door Laboratory Refrigerator  72 Cu. Ft. capacity  Three swing solid doors, self-closing, right hinged, not reversible  Microprocessor Temperature Controller  Adjustable operating temperature range: 1°-10°C  Standard Digital Temperature Display and Alarm Module with battery back-up to support temperature monitoring and alarms  Sample simulated digital temperature display; .1° Resolution  Adjustable temperature display in Celsius or Fahrenheit  Audible and visual high/low temperature alarms  2 probes; 1 in air and 1 in sample bottle  Sensor error alarm  Power failure alarm  Resettable 1-point Min/Max History  Remote alarm contacts  Alarm validation (audible, visual, and remote alarm)  Alarm mute with ring back  Twelve adjustable shelves (adjustable in ½" increments)  Forced draft air circulation  Keyed door lock  Magnetic door gasket for positive seal  Heavy duty door handle  LED interior lights are safety shielded and switch controlled  Swivel casters (3 ½")  probe access port (3/8")  White powder-coated steel exterior and interior  Hydrocarbon, natural refrigerant (R290)  Two year parts and labor warranty, plus an additional three compressor parts warranty  Exterior dimensions: 81" W x 34" D x 81 ¾" H with casters; 78 ¼" without casters  Cycle defrost  115V, 60 Hz, 7.5 Amps, 1/2 HP  ETL listed  Shipping weight: 600 lbs.</p>