

Product Name:	PH-ABT-HC-SSP-23
Description:	<p>Premier Pharmacy/Vaccine Stainless Steel Refrigerator 23 Cu. Ft. Capacity One stainless steel swing door, right hinged, not reversible Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts 2 probes; 1 in air and 1 in sample bottle Adjustable operating temperature range: 36°F – 46°F (2°C- 8°C) Refrigerator/Freezer freestanding thermometer with 3 year certificate of calibration, with min/max memory, °F/°C switchable Three adjustable shelves Vaccine storage power cord warning label Forced draft air circulation Keyed door lock Magnetic door gasket for positive seal Integrated door handle Swivel casters (adds 6 ½" to height) Interior light Probe access port (3/8") Stainless steel interior floor Stainless steel exterior High density urethane foam cabinet insulation Hydrocarbon, natural refrigerant (R290) Pharmacy refrigerator/freezer toolkit and temperature logs Two year parts and labor warranty, plus an additional three year compressor parts warranty Exterior dimensions: 26 ¾"W x 34 7/8"D x 83 7/8"H with casters; 77 3/8"H without casters Cycle defrost 115V, 60 Hz, 3 Amps, 1/5 HP ETL listed Shipping weight: 295 lbs.</p>

Product Name:	PH-ABT-HC-SSP-49
Description:	<p>Premier Pharmacy/Vaccine Stainless Steel Refrigerator 49 Cu. Ft. Capacity Two stainless steel swing doors Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts 2 probes; 1 in air and 1 in sample bottle Adjustable operating temperature range: 36°F – 46°F (2°C- 8°C) Refrigerator/Freezer freestanding thermometer with 3 year certificate of calibration, with min/max memory, °F/°C switchable Six adjustable shelves Vaccine storage power cord warning label Forced draft air circulation Keyed door locks Magnetic door gasket for positive seal Integrated door handles Swivel casters (adds 6 ½" to height) Interior light Probe access port (3/8") Stainless steel interior floor Stainless steel exterior High density urethane foam cabinet insulation Hydrocarbon, natural refrigerant (R290) Pharmacy refrigerator/freezer toolkit and temperature logs Two year parts and labor warranty, plus an additional three year compressor parts warranty Exterior dimensions: 54"W x 35"D x 84"H with casters; 77 ½"H without casters Cycle defrost 115V, 60 Hz, 4.5 Amps, 1/4 HP ETL listed Shipping weight: 450 lbs.</p>