

Product Name:	ABT-HC-10PG
Description:	<p>Premier Glass Door Compact Laboratory Refrigerator 10.5 Cu. Ft. Capacity One glass swing door, right hinged, not reversible Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts Adjustable operating temperature range: 1°C to 10°C Six adjustable shelves with guard rail on back to prevent product from being pushed against back wall Bottom footed shelf to allow air circulation Back wall evaporator cover Forced draft circulation Keyed door lock Magnetic door gasket for positive seal Leveling legs LED interior light Probe access port (3/8") Powder coat exterior High density urethane foam cabinet insulation HFC-free refrigerant (R600a), foam insulation and packaging Two year parts and labor warranty, plus an additional three year compressor parts warranty Quality certified with 100% unit temperature testing Exterior dimensions: 23 ¾"W x 26 ½"D x 59"H <i>Note: This unit must have 4" clearance on sides and back for adequate ventilation</i> UL/C-UL listed Cycle defrost 115V, 60 Hz, 1/3 HP, 2.3 Amps Shipping weight: 190 lbs.</p>

Product Name:	ABT-HC-10PS
Description:	<p>Premier Solid Door Compact Laboratory Refrigerator 10.5 Cu. Ft. Capacity One solid swing door, right hinged, not reversible Microprocessor temperature controller Digital temperature display Audible and visual high and low temperature alarms Remote alarm contacts Adjustable operating temperature range: 1°C to 10°C Six adjustable shelves with guard rail on back to prevent product from being pushed against back wall Bottom footed shelf to allow air circulation Back wall evaporator cover Forced draft circulation Keyed door lock Magnetic door gasket for positive seal Leveling legs LED interior light Probe access port (3/8") Powder coat exterior High density urethane foam cabinet insulation HFC-free refrigerant (R600a), foam insulation and packaging Two year parts and labor warranty, plus an additional three year compressor parts warranty Quality certified with 100% unit temperature testing Exterior dimensions: 23 ¾"W x 26 ½"D x 59"H <i>Note: This unit must have 4" clearance on sides and back for adequate ventilation</i> UL/C-UL listed Cycle defrost 115V, 60 Hz, 1/3 HP, 2.3 Amps Shipping weight: 175 lbs.</p>