

Product Name:	ABT-HCPTP-47
Description:	<p>Premier Pass Thru Laboratory Refrigerator  47 Cu. Ft. capacity  Two sliding glass doors on front, two solid swing doors on back  Microprocessor Temperature Controller  Adjustable operating temperature range: 1°-10°C  Digital Temperature Display and Alarm Module  Sample simulated digital temperature display; .1° Resolution  Adjustable temperature display in Celsius or Fahrenheit  Audible and visual high/low temperature alarms  Sensor error alarm  Power failure alarm  Resettable 1-point Min/Max History  Remote alarm contacts  Alarm validation (audible, visual, and remote alarm)  Alarm mute with ring back  Eight adjustable shelves  Keyed door lock  Magnetic door gasket for positive seal  Heavy duty door handle  Casters (adds 4" to height)  One probe access port (3/8")  White textured cabinet and door  High density urethane foam cabinet and door insulation  HFC-free refrigerant (R290a), foam insulation and packaging  Two year parts and labor warranty, plus an additional three year compressor parts warranty  Quality certified with 100% unit temperature testing  Exterior dimensions: 54 1/8"W x 32 3/8"D x 82 5/8" with casters;78 5/8 "H without casters  Cycle defrost  115V, 60 Hz, 8.8 Amps, ½ HP  UL/C-UL listed  Shipping weight: 575 lbs.</p>

Product Name:	ABT-HCPTP-49
Description:	<p>Premier Pass Thru Laboratory Refrigerator  49 Cu. Ft. capacity  Two sliding glass doors on front, two solid swing doors on back  Microprocessor Temperature Controller  Adjustable operating temperature range: 1°-10°C  Digital Temperature Display and Alarm Module  Sample simulated digital temperature display; .1° Resolution  Adjustable temperature display in Celsius or Fahrenheit  Audible and visual high/low temperature alarms  Sensor error alarm  Power failure alarm  Resettable 1-point Min/Max History  Remote alarm contacts  Alarm validation (audible, visual, and remote alarm)  Alarm mute with ring back  Eight adjustable shelves  Keyed door lock  Magnetic door gasket for positive seal  Casters (adds 4" to height)  Heavy duty door handle  One probe access port (3/8")  White textured cabinet and door  High density urethane foam cabinet and door insulation  HFC-free refrigerant (R290a), foam insulation and packaging  Two year parts and labor warranty, plus an additional three year compressor parts warranty  Quality certified with 100% unit temperature testing  Exterior dimensions: 54 1/8" W x 33 7/8"D x 82 5/8"H with casters;  78 5/8"H without casters  Cycle defrost  115V, 60 Hz, 8.5 Amps, 1/2 HP  UL/C-UL listed  Shipping weight: 575 lbs.</p>