

Premier Compact Laboratory Refrigerators

Premier Compact Laboratory Refrigerators

The Premier compact laboratory Refrigerators feature a microprocessor temperature controller and display, allow for precise temperature control, verification and recovery versus mechanical style thermostats.

An interior fan driven, forced-draft air circulation system provides excellent temperature uniformity and recovery after door openings. Critical samples and supplies are security backed with an extensive package of audible and visual alarms.





The Premier Compact Refrigerators take a large step forward in performance from past solid door general purpose units; offering a Digital temperature display and alarm module coupled with a microprocessor temperature controller.

6 Adjustable shelves with guard rail on back to prevent product from being pushed against back wall.



ABT-HC-RFC10PG

These models require 4" of clearance around back and sides of the unit for proper ventilation. Improper installation will void the warranty and will lead to temperature maintenance issues, overheating and possible failure.

Model	Cu. Ft.	Defrost	Doors	Shelves	W"	D"	H"	RL	H.P.	Amps
ABT-HC-10PG 	10.5	Cycle	1 Glass	6 Adj	23 3/4	26 1/2	59	R600a	1/3	2.3
ABT-HC-10PS 	10.5	Cycle	1 Solid	6 Adj	23 3/4	26 1/2	59	R600a	1/3	2.3



- Microprocessor temperature controller
- Digital temperature display
- Audible and visual high and low temperature alarms
- Remote alarm contacts
- Adjustable operating temperature range: 1°C to 10°C
- Bottom footed shelf to allow air circulation
- Back wall evaporator cover
- Forced draft circulation
- Keyed door lock
- Magnetic door gasket for positive seal
- Leveling legs
- LED interior light
- Probe access port (3/8")
- Powder coat exterior
- High density urethane foam cabinet insulation
- HFC-free refrigerant (R600a), foam insulation and packaging
- Two year parts and labor warranty, plus an additional three year compressor parts warranty
- Quality certified with 100% unit temperature testing
- Note: This unit must have 4" clearance on sides and back for adequate ventilation
- UL/C-UL listed
- Cycle defrost