

# TempLog Premier Glass & Solid Door Laboratory Refrigerators

## TempLog Premier Glass & Solid Door Laboratory Refrigerators

The TempLog Premier Glass & Solid Door Laboratory Refrigerators are purpose built for scientific and medical applications.

Units feature a digital microprocessor temperature controller, a forced air directional refrigeration system, and an automatic cycle-defrost design prevents product damaging temperature spikes.

Sample simulated temperature display to show real-time product temperatures.



Environmentally friendly, natural hydrocarbon (HC) refrigerants which vastly reduce global-warming potential while meeting new EPA/SNAP mandates.

Model	Cu. Ft.	Defrost	Doors	Shelves	W"	D"	H"	RL	H.P.	Amps
ABT-HC-19-TS	19	Cycle	1 Swing Glass	4 Adj	27	26 3/8	78 5/8	R290a	1/3	5.4
ABT-HC-19-TS-LH	19	Cycle	1 Swing Glass	4 Adj	27	26 3/8	78 5/8	R290a	1/3	5.4
ABT-HC-23-TS	23	Cycle	1 Swing Glass	4 Adj	27	31 3/8	78 5/8	R290a	1/3	5.4
ABT-HC-26-TS	26	Cycle	1 Swing Glass	4 Adj	30	31 3/8	78 5/8	R290a	1/3	5.4
ABT-HC-47-TS	47	Cycle	2 Slide Glass	8 Adj	54 1/8	33 3/8	78 5/8	R290a	1/2	9.6
ABT-HC-49-TS	49	Cycle	2 Swing Glass	8 Adj	54 1/8	31 3/8	78 5/8	R290a	1/2	8.5
ABT-HC-69-TS	69	Cycle	3 Slide Glass	12 Adj	78 1/8	33 3/8	78 5/8	R290a	3/4	6.5
ABT-HC-72-TS	72	Cycle	3 Swing Glass	12 Adj	78 1/8	33 3/8	78 5/8	R290a	1/2	8.5



- Microprocessor temperature controller
  - Adjustable operating temperature range: 1°C - 10°C
  - Touch Screen Digital Temperature Display and Alarm Module
  - Password-protected control panel
  - Sample simulated digital temperature display; 1° Resolution, adjustable temperature display in Celsius or Fahrenheit
  - Active temperature scale bar display
  - Resettable 1-point min/max history
  - Digital 24-hour temperature chart
  - Temperature data logging
- USB port for data transfer and software updates
  - Real-time operational display clock
  - 4-20mA output
  - Electronic troubleshooting guide
  - Electronic QR Code to access Owner's Manual & technical support contact Information
  - Adjustable alarm volume
  - Audible and visual high/low temperature alarms
  - Sensor error alarm
  - Power failure alarm